



0950 29
70W HP Sodium - ceiling



0952 41 + 0950 73
100W HP Sodium - pole 25°



0950 68 150W
HP Sodium - wall



0952 68 + 0950 74
400W mercury vapour - pole 90°

70 to 400 W wellglass luminaires

- Power supply 230/240 V (+ 6% - 10%) 50 Hz
- Instant relighting with auxiliary halogen lamps, depending on model, (lamps not supplied)
- Wellglass dimensions on page 62
- Fast relighting for 70 W and 150 W sodium: 5 to 30 seconds depending on the duration of the mains power supply failure
- Optional fibre glass reinforced polyester reflector (see accessories)
- Painted aluminium body and fixings
- High temperature silicone gasket
- Connection via terminal block (2 x 4 mm² max.)
- Ceiling mounting: Four M20 threaded cable entries, supplied with three blanking plugs
- Wall mounting: Four M20 threaded cable entries, supplied with three blanking plugs
- Mounting under tube: One 3/4 NPT cable entry (possible adaptor for M20)
- Pole mounting: One 1" 1/4 NPT cable entry

Fixings on ceiling or under tube

	Weight (Kg)	Volume (dm ³)	Cat. No. Wall	Cat. No. Conduit	Pack
High pressure sodium					
70 W	7.4	39	0950 29	0950 59	1
100 W	9	55	0951 32	0951 40	1
150 W	9	55	0950 67	0950 66	1
150 W + 2 x 150 W halogen	14	70	0951 35	0950 62	1
250 W	16	70	0950 30	0950 50	1
400 W	19	85.2	0950 31	0950 51	1
Incandescent					
100 W	7.4	39	0951 33	0951 41	1
150 W	7.4	39	0951 37	0951 45	1
Halogen					
100 W	7.4	39	0951 33	0951 41	1
150 W	7.4	39	0951 37	0951 45	1
Mercury vapour					
125 W	7.4	39	0951 34	0951 42	1
250 W	14	70	0950 32	0950 52	1
400 W	19	85.2	0951 39	0951 47	1
Metal halide					
150 W	9	55	0951 36	0951 43	1
250 W	16	70	0951 38	0951 46	1
400 W	19	85.2	0950 34	0950 54	1

Wall or pole mounting

	Weight (Kg)	Volume (dm ³)	Cat. No. wall	Cat. No. 25° pole	Cat. No. 90° pole	Pack
High pressure sodium						
70 W	7.4	39	0950 60	0950 61	0952 55	1
100 W	9	55	0951 48	0952 41	0952 56	1
150 W	9	55	0950 68	0950 69	0952 59	1
150 W + 2 x 150 W halogen	14	70	0950 64	0950 65	0952 60	1
250 W	16	70	0950 40	0952 46	0952 64	1
400 W	19	85.2	0950 41	0952 49	0952 67	1
Incandescent						
100 W	7.4	39	0952 15	0952 42	0952 57	1
150 W	7.4	39	0952 18	0952 45	0952 62	1
Halogen						
100 W	7.4	39	0952 15	0952 42	0952 57	1
150 W	7.4	39	0952 18	0952 45	0952 62	1
Mercury vapour						
125 W	7.4	39	0952 16	0952 43	0952 58	1
250 W	14	70	0952 19	0952 47	0952 65	1
400 W	19	85.2	0952 21	0952 51	0952 68	1
Metal halide						
150 W	9	55	0952 17	0952 44	0952 61	1
250 W	16	70	0952 20	0952 48	0952 66	1
400 W	19	85.2	0952 22	0952 52	0952 69	1

Accessories

Dome reflectors

	Cat. No.	Pack
70 W to 150 W wellglass luminaires (except 150 W + 2 x 150 W halogen)	0950 70	1
150 W HP sodium + (2 x 150 W halogen) wellglass luminaires	0956 76	1
250 W and 400 W wellglass luminaires	0956 76	1

30° reflector

70 W to 150 W wellglass luminaires (except 150 W + 2 x 150 W halogen)	0950 71	1
150 W HP sodium + (2 x 150 W halogen) wellglass luminaires	0950 72	1
250 W and 400 W wellglass luminaires	0950 72	1

Guard

70 W to 150 W wellglass luminaires (except 150 W + 2 x 150 W halogen)	0950 73	1
150 W HP sodium + (2 x 150 W halogen) wellglass luminaires	0950 74	1
250 W and 400 W wellglass luminaires	0956 74	1

For special options, please consult us

- Other voltages
- Refractor

Technical data (see page 62)