



0931 08



0931 16

For 2 pole, 3 pole and 4 pole MCBs

- Grey painted aluminium alloy box
- 2 x M20 entries positioned vertically (cable gland not supplied)
- Front control via rotary switch handle (supplied)
- Can be padlocked using switch handle Cat. No. 0940 01

Catalogue numbers

	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
For LEXIC/DX MCBs from 1 to 40 A, 2-pole, 3-pole and 4-pole	3.8	11	0931 08	1

For 2 pole RCBOs

- Grey painted aluminium alloy box
- 2 x M20 entries positioned vertically (cable gland not supplied)
- Front control via rotary switch handle (supplied)
- Can be padlocked using switch handle Cat. No. 0940 01
- Black test button on front face

Catalogue numbers

	Weight (Kg)	Volume (dm ³)	Cat. No.	Pack
For 1 to 40 A LEXIC/DX MCBs, 30 mA and 300 mA 2 pole RCBOs	3.9	11	0931 16	1

For special options, please consult us:

- Other threads
- Other ratings

Customised control stations and electrical accessory boxes (see page 222)

Flameproof cable glands (see page 252)



Part number in bold : fast moving references

Zones 1 & 2 - 21 & 22	ATEX	IEC	EC	II 2 G/D
Ex d IIB	T4 or T3	T = 135°C	IP66	IK10

TECHNICAL DATA

Zones : 1 and 2 and 21 - 22

Classification :

- According to CENELEC:
 - Conforming to ATEX directive 94/9 EC and standards EN 50014-18
 - EC 0081 II 2 G for gas Ex d IIB T4 for Ta < + 40°C and T3 for + 40°C < Ta < + 55°C
 - EC 0081 II 2 D - T = + 135°C for dust
- According to IEC:
 - Conforming to standards IEC 60079-0/1 Ex d IIB T3 for Ta < + 40°C and T3 for + 40°C < Ta < + 55°C
 - DIPA 21 TA = + 135°C

Certification :

- Approved type CF2D
- CENELEC LCIE 03 ATEX 6061X
- IEC LCIE Ex 03 006 X
- declaration of conformity No. 50254
- Conforming to standards EN 50281-1-1 and IEC 61241-1-1
"combustible dust"

Protection index :

- IP66 according to EN 60529 and IEC 60529
- IK10 mechanical resistance according to EN 50102

Anticorrosion treatment and climate protection : see page G50

Operating temperature : - 40°C to + 55°C

Dimensions (mm) :

