

# ATX™ FU40 Series Fuse Carrier

## Components for Increased Safety Enclosures


ATEX/IECEx: Zones 1 and 2  
 Notable: UKEX, INMETRO Certified

### Applications

- Useful as back-up fuse protection or as main fuse protection for hazardous locations.
- Can be fitted inside increased safety Ex e enclosures.

### Features

- For 14 mm x 51 mm (0.55" x 2.01") cylindrical cartridge fuse 40A gG Max. and 40A aM Max.
- Adaptor which clips onto EN 50 022 and EN 50 035 rail.
- Connection via 2.5 mm<sup>2</sup> x 16 mm<sup>2</sup> (0.09 in<sup>2</sup> x 0.62 in<sup>2</sup>) terminals.



### Standard Material

- Polyamide

### ATEX/IECEx Certifications and Compliances

- Certification Type: FU40
  - Gas, Zones 1 and 2
    - Conforming to ATEX 2014/34/EU: Ⓜ II 2 G
    - Type of Protection: Ex db eb IIC Gb
- Service Temperature: -40 °C to +90 °C (-40 °F to +194 °F)
- ATEX Certificate: LCIE 15 ATEX 3014U
- IECEx Certificate: IECEx LCIE 15.0007U

### UKEX Certifications

- UKEX Certificate: CML21UKEX3188U

### INMETRO Certifications

- INMETRO Certificate: BVC11.0593-U

Weight kg (lb)	Volume dm <sup>3</sup> (in <sup>3</sup> )	Fuse Size mm (in)	In max	Un max	Catalog Number
0.1 (0.22)	0.4 (24.4)	14 x 51 (0.55 x 2.01)	40A	690V	FU40

### Dimensions in Millimeters (Inches)

